

UNCLASSIFIED

AD 272 349

*Reproduced
by the*

**ARMED SERVICES TECHNICAL INFORMATION AGENCY
ARLINGTON HALL STATION
ARLINGTON 12, VIRGINIA**



UNCLASSIFIED

BEST AVAILABLE COPY

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

BEST AVAILABLE COPY

CATALOGED BY ASTIA

AS AD No. 272349

272 349

RESISTORS, VARIABLE
(FILM TYPE)

QUARTERLY PROGRESS REPORT #14
1 SEPTEMBER THROUGH 30 NOVEMBER 1961


CONTRACT NO. DA-36-039-SC-75981
ORDER NO. 43796-PP-58-81-81

Prepared for the U. S. Army Signal Agency

by

ENGINEERING AND RESEARCH DIVISION

INTERNATIONAL RESISTANCE COMPANY



BEST AVAILABLE COPY

RESISTORS, VARIABLE

(FILM TYPE)

QUARTERLY PROGRESS REPORT #14

1 SEPTEMBER THROUGH 30 NOVEMBER 1961

Contract No: DA 36-039-SC-75981-
Order No: 43796 PP-58-81-81
Applicable Specification: M.L. R. 94B (Modified)
Report Prepared at: International Resistance Co.
401 North Broad Street
Philadelphia 8, Penna.
Prepared By:

John Woods
Senior Product Development Engineer

Approved By:

Harry Casey
Project Leader



Sava I. Sherr
Manager, Government Operations

"The work reported under this document has been made possible through the support and sponsorship extended by the U. S. Army Signal Agency under Order No. 43796-PP-58-81-81. It is published for technical information only and does not necessarily represent recommendations or conclusions of the sponsoring Agency."

TABLE OF CONTENTS

| | <u>PAGE</u> |
|-----------------------------|-------------|
| Abstract | 3 |
| Background | 4 |
| I. Product Engineering | 7 |
| A. Substrates | 7 |
| B. Testing - Pre-Production | 8 |
| II. Pre-Production | 11 |
| III. Facilities | 11 |
| A. Element | 11 |
| B. Housing | 12 |
| Conclusions | 13 |
| Program for Next Quarter | 14 |
| Personnel | 15 |
| Appendix | 16 |

ABSTRACT

Acceptable RV12 substrates have been received from American Lava.

Pre-pre-production tests and subsequent results obtained with unhoused elements show that moisture resistance can be improved with a thin film coating or a slight revision in termination material. Moisture failures appear to be greatly reduced by running the test without housings; indicating that moisture entrapment in the housings has been a major hindrance to good performance.

Manicuring of facilities continues as required.

An improved method of applying the silver shorting path for "C" tapers, which involves spraying through a mask in place of the silk screening method now used, has been developed.

BACKGROUND

The purpose of this contract is to develop, design, procure, install and maintain manufacturing facilities to produce variable film-type resistors capable of satisfying MIL-R 94B (as modified in accordance with Contract No. DA-36-039-SC-75981) whose major characteristics include 125°C ambient temperature, 100,000 cycle operation at ambient with rated load, and improved environmental stability.

In a Technical Action Request dated July 18, 1959, RC proposed changes in the applicable components specifications. Subsequently, with one exception, the requested changes were approved. The exception involved rotational life characteristics and the possibility of future approval was made contingent upon the submission by RC of further technical information. The most significant change involved noise level before and after rotation. This ENR level must (1) not exceed 1% of total resistance or 5 ohms (whichever is greater), (2) nor may it exceed 5% of total resistance or 25 ohms (whichever is greater), after 100,000 cycle operation, full rated load at 125°C or de-rated load at 150°C.

As a result of the signing of an operation agreement between IRC and Chicago Telephone Supply Service of Elkhart, Indiana, it was decided that IRC and CTS would submit a proposal to the USASSA allowing establishment of facilities at CTS.

The development program to date has been directed toward the establishment of a system (substrate, film and contact) which is capable of meeting the contract requirements. After considerable effort, this system has been incorporated into a potentiometer design.

Carbon alloy, metal, and glaze films have been tested on ceramic substrates using molded carbons, precious metals and carbongraphite wiper materials. While both metal film and resistive glaze elements showed some promise, the performance levels were not as high as those observed for carbon alloy.

After considerable difficulty experienced by Coors Porcelain Company in making substrates in the designed configuration, another vendor (American Lava) has tooled to produce 96% alumina substrates for both the RV11 and RV12 potentiometers. The surface finish requirement of these

substrates has been established at 15 microinches, and carbon alloy has been selected for deposition on the substrates. A single grade of carbon (Pure Carbon Co. E-27) will be used as the wiper on all resistance ranges from 100 ohms through 1,000,000 ohms.

The method of adjusting resistance tolerance as reported in Quarterly Report #7, on production elements is operational. The screening of a pattern of conductive material to produce nonlinear taper has been proved feasible.

Temperature coefficient curves indicate that for linear elements, 750 PPM can be maintained for resistance of 100,000 ohms and less. At 200,000 ohms, 750 PPM becomes marginal and 1500 PPM is exceeded for all values of 400,000 ohms and greater. Temperature coefficient on "C" tapered elements will correspond to those values observed on linear elements which are approximately double the resistance range of the tapered element.

An improved termination of VZA conductive paint with a VLS carbon ink overlay provides moisture resistance superior to that of VZA alone. However, moisture tests of housed elements have shown a high failure rate, indicating that the sealed housing has a deleterious effect.

I. PRODUCT ENGINEERING

A. Substrates

Deliveries of 1500 RV12 substrates have been received from American Lava. Dimensions are acceptable with the following deviations noted: 1) the $.968 \pm .005$ outside diameter is undersized on most pieces, measuring .956 to .959; 2) the inner wall in the terminal slot area has been made thicker by addition of a radial contour, whereas, the drawing specifies two chords of the inside diameter. Deviation 1) has been accepted after checking with CTS to confirm that the substrate can be clinched in the clinching ring; 2) is a minor deviation having no effect on processing or assembling the element.

A small lot (271) of RV11 substrates were rejected, and returned to vendor, for high surface roughness. A sample of six pieces averaged 19.4 microinch RMS with a span of 18 to 22 microinch.

B. Testing

The pre-pre-production tests, representing the first data obtained with the carbon alloy elements assembled in housings, have been completed. Most of the data was reported in Quarterly Report #13. The completed data summaries are presented here (Tables II through V.). As previously noted, load life and rotational life changes were greater than the specified $\pm 5\% \Delta R$. Some of the larger load-life changes were attributed to substrate and termination defects. Process changes have been made to correct these conditions. Because one lot each of RV11 and RV12 units was found to have been improperly mounted on heat sinks during the load life test, the test was repeated (test lots No. 14200 and 14201 in Table II) with potentiometers assembled at the same time as those previously tested. The resistance changes were again high. Disassembly of the units having the greatest changes showed that the terminations were thin and incomplete, as was noted before.

Another defect visible in the RV12 pots is an inadequate crimping of the clinching ring which prevents proper seating of the substrate against the ring. This decreases the heat conduction to the housing causing excessive film temperature. CTS will be advised of the situation so that corrections can be made before pre-production.

The major problem which showed up in pre-pre production testing was poor performance in the moisture resistance test.

Data obtained in the last quarter (Quarterly Progress Report #13) indicated that a carbon ink overlay covering the VZA termination would improve moisture resistance. A lot of 12 RV11 potentiometers were assembled with the improved termination. All openings in the housing were sealed with epoxy; and in four assemblies, the opening between the shaft and bushing was also sealed. The latter operation prevents rotation of the shaft, but was used in this instance to determine whether or not an improved shaft seal is necessary. Half of the pots were submitted to the MIL-R-94B moisture resistance test at IRC; and half at CTS.

All of the units which had been sealed around the shaft, and 4 of the 8 other units, were "open" after 10 moisture cycles. (See Table I.)

In an effort to improve moisture resistance of the element itself, 10 groups of unhoused elements were prepared and submitted to the moisture test. These groups used various protective coatings and termination modifications, as shown in Table VII. This table also summarizes the test results after 10 moisture cycles. Group numbers 4, 5, 8, 9, and 10 had no failures. There were no "opens" in any group, including group 6 which was terminated in the same manner as were the assembled pots of Table I. Moisture cycling of the unhoused elements is continuing in order to determine the best system.

It is apparent from the findings to date that the sealed housing is a detriment to good moisture resistance. In future assemblies, the housing will be left completely unsealed to allow entrapped moisture to escape.

II. PRE-PRODUCTION

Production of elements was stopped pending evaluation and solution of the moisture problem. Manufacture of pre-production elements will be started, using the revised termination and/or coating indicated by the tests in i B. above.

"C" taper shorting patterns have been successfully screened. Because of the fine resolution required in the RVII pattern, the consistency of the VZA is critical, and the screen must be cleaned frequently.

III. FACILITIES

A. Element

The element facility changes during the past quarter consisted of some minor mancuring of the equipment and the development of an improved technique for applying the taper shorting path.

The screening set-up for tapers was brought to the point where the taper pattern could be screened on the elements consistently. As pointed out above, the screening material viscosity is critical, however, the system is workable.

An alternative method of applying the same pattern was developed. It was demonstrated that a mask could be made by the photo-etch process which retained sharp definition. The silver was sprayed through this mask and the resulting pattern was acceptable. The operation is less critical than screening so this method will be tooled.

A checking fixture for reading resistance at the mid rotation point of the elements was made.

Also, an improved contactor of Pallinoy #7 Alloy was made to monitor the resistance of an element while adjusting it on the machine.

B.

Housing

No changes to report.

CONCLUSIONS

1. Acceptable substrates can be produced for both the RV11 and RV12 sizes.
2. Moisture results obtained with unboxed elements are superior to data obtained with assembled, epoxy-sealed potentiometers.
3. Definition and ease of application of the "C" taper pattern are improved by the use of a photo-etched mask and spray in place of the silk screening process.

PROGRAM FOR NEXT QUARTER

1. The moisture tests on unhoused elements will be continued to determine which termination and/or coating provides the most protection.
2. Pre-production of elements will be begun using the indicated new termination.

PERSONNEL

| <u>Engineering</u> | <u>Hours</u> |
|---|--------------|
| J. Woods | 136.0 |
| M. Steidlitz | 58.5 |
| <u>Mechanical, Chemical, Electrical Development</u> | |
| F. Surowiec | 21.0 |
| E. Dietrich | 15.0 |
| E. Altorfer | 2.0 |
| W. Gold | 20.0 |
| <u>Technicians</u> | |
| B. Kelly | 157.5 |
| O. Leidic | 66.5 |
| A. Graft | 40.0 |
| G. Williams | 40.0 |
| D. Terry | 136.5 |
| E. Greenleaf | 76.0 |
| T. Arline | 40.0 |
| <u>Test Section</u> | <u>124.7</u> |
| Total IRC | 933.7 |
| Total CTS | <u>44.0</u> |
| TOTAL | 977.7 |

APPEND X

| <u>TABLE</u> | <u>PAGE</u> |
|---|-------------|
| 1. Moisture Resistance Test of 325K RV Potentiometers | 17 |
| 2. Pre-Production Tests RV 185K | 18 |
| 3. Pre-Production Tests T.C Load-Life | 19 |
| 4. Pre-Production Tests Vibration Moisture | 20 |
| 5. Pre-Production Tests Solder Rotation | 21 |
| 6. Pre-Production Tests General | 22 |
| 7. Moisture Tests - Unhoused RV Elements | 23 |

TABLE I

Moisture resistance tests of 325K Ω RVII potentiometers (combined IRC and CTS results).

| No. Units | (% Δ R (spec: $\pm 5\%$)) | | | Fail | Remarks |
|-----------|-----------------------------------|-------|----------------------|-------------------|--|
| | Max | Min. | Ave. | | |
| 8 | +4.6 | +0.81 | +2.05 (ave. of 4) | 4/8 (4 "open") | Units epoxy sealed on back of element and between case and bushing |
| 4 | ALL UNITS "OPEN" | | | 4/4 | Units sealed as above, plus epoxy seal around shaft. |

Note: All units passed 500 V AC dielectric strength; 1/12 failed insulation resistance: 40 M Ω (spec. 100 M Ω minimum).

3-303-1

| PREPARED BY AK, JW | | TITLE | | PRE-PRODUCTION TESTS - FILM POTENTIAL 185KΩ | | | | | | | | | |
|-----------------------------|------|--|--------|--|--------|--------|--|---------|---------|----------|--|--|--|
| CHECKED BY | | | | | | | | | | | | | |
| APPROVED BY | | | | | | | | | | | | | |
| RESISTANCE & DATA NO. | | TEMPERATURE COEFFICIENT SPEC: 750000/Ω | | | | | SPEC: 1.34% 1.76% 2.16% MAX LOAD LIFE 125°C ± 150°C | | | | SPEC: 1.34% 1.76% 2.16% MAX LOAD LIFE 125°C ± 150°C | | |
| | | PPM/°C | PPM/°C | PPM/°C | PPM/°C | PPM/°C | %ΔR | %ΔR | %ΔR | %ΔR | | | |
| | | -15°C | -55°C | +25°C | +105°C | +165°C | 96 HRS | 192 HRS | 528 HRS | 1008 HRS | | | |
| FILM POT. (1PG) | AV | -947 | -872 | -722 | -704 | -684 | +0.34 | +0.50 | +0.77 | +0.71 | 125°C FULL LOAD | | |
| RV-11 | SPAN | -232 | -774 | -653 | -629 | -603 | +0.32 | +0.23 | +1.06 | +1.11 | | | |
| 185KΩ 1/2W | FAIL | -998 | -916 | -788 | -763 | -746 | +0.35 | +0.60 | +0.65 | +0.46 | | | |
| 08227 | FAIL | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | | | |
| FILM POT. (1PG) | AV | -844 | -785 | -663 | -636 | -612 | +0.34 | +0.44 | +1.19 | +0.57 | 150°C 40% LOAD | | |
| RV-11 | SPAN | -790 | -731 | -613 | -585 | -555 | +0.42 | +0.52 | +0.80 | +1.40 | | | |
| 185KΩ 1/2W | FAIL | -790 | -863 | -555 | -711 | -697 | -0.50 | -0.50 | -3.32 | +0.07 | | | |
| 08228 | FAIL | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 | | | |
| FILM POT. (1PG) | AV | | | | | | | | | | | | |
| RV-11 | SPAN | | | | | | | | | | | | |
| 185KΩ 1/2W | FAIL | | | | | | | | | | | | |
| 08229 | FAIL | | | | | | | | | | | | |
| FILM POT. (1PG) | AV | | | | | | | | | | | | |
| RV-11 | SPAN | | | | | | | | | | | | |
| 185KΩ 1/2W | FAIL | | | | | | | | | | | | |
| 08230 | FAIL | | | | | | | | | | | | |
| | AV | | | | | | | | | | | | |
| | SPAN | | | | | | | | | | | | |
| | FAIL | | | | | | | | | | | | |
| | AV | | | | | | | | | | | | |
| | SPAN | | | | | | | | | | | | |
| | FAIL | | | | | | | | | | | | |
| | AV | | | | | | | | | | | | |
| | SPAN | | | | | | | | | | | | |
| | FAIL | | | | | | | | | | | | |
| | AV | | | | | | | | | | | | |
| | SPAN | | | | | | | | | | | | |
| | FAIL | | | | | | | | | | | | |
| | AV | | | | | | | | | | | | |
| | SPAN | | | | | | | | | | | | |
| | FAIL | | | | | | | | | | | | |
| | AV | | | | | | | | | | | | |
| | SPAN | | | | | | | | | | | | |
| | FAIL | | | | | | | | | | | | |
| | AV | | | | | | | | | | | | |
| | SPAN | | | | | | | | | | | | |
| | FAIL | | | | | | | | | | | | |

1

1

BEST AVAILABLE COPY

X 3-303-1

| PREPARED BY <i>RK, 1W</i> | | TITLE <i>PRE-PRODUCTION TESTS</i> | | | | TYPE RV11 RV12 | | DWG. NO. <i>B</i> | | TABLE <i>III</i> | |
|-------------------------------------|------|---|--------------|---------------|---------------|----------------------|------------------------|---------------------|---------|------------------|--------------|
| CHECKED BY | | | | | | | | DATE <i>9-18-61</i> | | | |
| APPROVED BY | | | | | | | | | | | |
| RESISTANCE & DATA NO. | | TEMPERATURE COEFFICIENT <small>RV11: 150 PPM TO 250K & 150 PPM TO 175K RV12: 750 PPM TO 500K & 750 PPM TO 175K</small> | | | | | LOAD LIFE SPEC: 15% | | | | |
| | | -15°C PPM | -25°C PPM | +125°C PPM | +175°C PPM | +650°C PPM | 26 HRS | 192 HRS | 504 HRS | 1008 HRS | TEMP LOAD |
| RV12 2W 70KΩ 11120 | AV | -362 | -362 | -315 | -318 | -304 | +4.25 | +3.99 | +3.5 | +20.6 | |
| | SPAN | -380 | -383 | -335 | -329 | -321 | +9.93 | +9.44 | +7.24 | +58.74 | 150°C |
| | FAIL | -353 | -348 | -290 | -306 | -282 | +1.31 | +1.11 | +1.39 | +1.35 | 0.2W |
| RV11 1/2W 1PC. 350KΩ 11296 | AV | -1643 | -1762 | -1191 | -1173 | -1051 | +1.69 | +0.98 | +2.89 | +2.93 | |
| | SPAN | -1750 | -1888 | -1290 | -1253 | -1106 | +1.98 | +1.21 | +2.71 | +3.68 | 150°C |
| | FAIL | -1508 | -1664 | -1095 | -1074 | -956 | +1.49 | +0.72 | +2.17 | +2.46 | 0.2W |
| RV11 1/2W 3PC. 250KΩ 11121 | AV | -1125 | -1205 | -851 | -888 | -902 | +4.77 | +4.0 | +5.65 | +14.93 | |
| | SPAN | -1138 | -1224 | -880 | -898 | -936 | +8.62 | +7.36 | +7.14 | +24.21 | 150°C |
| | FAIL | -1118 | -1194 | -828 | -875 | -864 | +0.85 | +0.63 | +1.05 | +5.45 | 0.2W |
| RV12 2W 70KΩ 11118 | AV | -349 | -341 | -344 | -342 | -349 | +1.16 | +4.10 | +4.35 | +5.65 | |
| | SPAN | -365 | -365 | -368 | -355 | -372 | +6.30 | +5.91 | +9.34 | +12.48 | 125°C |
| | FAIL | -283 | -296 | -325 | -326 | -326 | +1.19 | +1.34 | +1.46 | +4.08 | FULL |
| RV11 1/2W 1PC. 350KΩ 11297 | AV | -1646 | -1728 | -1135 | -1151 | -1025 | +3.70 | +4.95 | +11.16 | +11.16 | |
| | SPAN | -1507 | -1604 | -1220 | -1213 | -1173 | +8.26 | +10.74 | +17.87 | +17.87 | 125°C |
| | FAIL | -1522 | -1556 | -1025 | -1064 | -1064 | +0.42 | +0.91 | +4.45 | +4.45 | FULL |
| RV11 1/2W 2PC. 350KΩ 11119 | AV | -1131 | -1176 | -822 | -888 | -770 | +2.86 | +6.52 | +6.76 | +11.46 | |
| | SPAN | -1158 | -1224 | -975 | -934 | -844 | +4.99 | +8.45 | +8.42 | +13.75 | 125°C |
| | FAIL | -1085 | -1129 | -825 | -835 | -836 | +0.45 | +5.54 | +5.11 | +7.57 | FULL |
| RV12 2W 70KΩ 12901 | AV | | | | | | +3.40 | +3.91 | +8.45 | +11.46 | |
| | SPAN | | | | | | +5.57 | +6.39 | +11.52 | +11.52 | 125°C |
| | FAIL | | | | | | +1.10 | +1.17 | +2.44 | +2.44 | FULL |
| RV11 1/2W 350KΩ 14100 | AV | | | | | | +3.55 | +6.80 | +8.86 | +10.41 | |
| | SPAN | | | | | | +1.11 | +12.19 | +12.3 | +27.21 | 125°C |
| | FAIL | | | | | | +0.17 | +3 | +12.33 | +11.77 | FULL |
| RV12 2W 70KΩ 14201 | AV | | | | | | +2.85 | +1.44 | +5.64 | +7.73 | |
| | SPAN | | | | | | +3.18 | +4.00 | +12.61 | +17.22 | 125°C |
| | FAIL | | | | | | +0.18 | +0.25 | +0.25 | +0.74 | FULL |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |
| | SPAN | | | | | | | | | | |
| | FAIL | | | | | | | | | | |
| | AV | | | | | | | | | | |

① ONE UNIT OPEN; NOT IN AVE.
ON SPAN

- NOTE:-
1. FAILURE RATE FOR TC ON RV11, 250KΩ ASSUMES 1500 PPM SPEC.
 2. UNITS OF #11297 & 12901 NOT PROPERLY MOUNTED ON HEAT SINK.

X 3-303-1

| PREPARED BY BK, JN | | TITLE PRE-PRODUCTION TESTS | | TYPE RV11 RV12 | | DWG. NO. B | | TABLE IV | |
|----------------------------|------|----------------------------|-----------|----------------|------------|-----------------------|---|----------|---|
| CHECKED BY | | | | | | DATE | | 9-18-61 | |
| APPROVED BY | | | | | | | | | |
| RESISTANCE & SPEC DATA NO. | | VIBRATION TESTS MAX | | MOISTURE | | | | | |
| | | RV11-15% | RV12-15% | ± 5% | 100M2 | | | | |
| | | 900K 900K | 900K 900K | MINI. TEST | DIELECTRIC | INSUL. RES | | | |
| | | TOTAL 50% | 400K | | | MEG. Ω | | | |
| RV12 2W | AV | ± 0.17 | ± 0.18 | ± 6.90 | | 12.71x10 ² | | | |
| 90K-2 | SPAN | + 0.44 | + 0.42 | 117.57 | | 30x10 ² | | | |
| 11110 | FAIL | + 0.06 | + 0.20 | - 0.66 | | 14.71x10 ² | | | |
| | | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| RV11-1 PL | AV | ± 0.07 | + 0.86 | ALL | | | | | |
| 1/2 W | SPAN | + 0.25 | + 5.29 | OPEN | | | | | |
| 350K-2 | FAIL | + 0.06 | + 0.81 | | | | | | |
| 11294 | | 0 | 0 | 0 | 0 | | | | |
| RV11-2 PL | AV | + 0.27 | ± 0.57 | + 3.66 | | 165.6x10 ² | | | |
| 3/4 W 250K-2 | SPAN | + 0.26 | 10.09 | + 6.34 | | 500x10 ² | | | |
| 11111 | FAIL | + 0.15 | - 1.20 | + 0.98 | | 4.5x10 ² | | | |
| | | 0 | 0 | 3 ③ 4 | 0 | 4 | 0 | 4 | 4 |
| | AV | | | | | | | | |
| | SPAN | | | | | | | | |
| | FAIL | | | | | | | | |
| | AV | | | | | | | | |
| | SPAN | | | | | | | | |
| | FAIL | | | | | | | | |
| | AV | | | | | | | | |
| | SPAN | | | | | | | | |
| | FAIL | | | | | | | | |
| | AV | | | | | | | | |
| | SPAN | | | | | | | | |
| | FAIL | | | | | | | | |
| | AV | | | | | | | | |
| | SPAN | | | | | | | | |
| | FAIL | | | | | | | | |
| | AV | | | | | | | | |
| | SPAN | | | | | | | | |
| | FAIL | | | | | | | | |
| | AV | | | | | | | | |
| | SPAN | | | | | | | | |
| | FAIL | | | | | | | | |
| | AV | | | | | | | | |
| | SPAN | | | | | | | | |
| | FAIL | | | | | | | | |

① = NO. OF TESTS NOT INCL.
IN AVE OR MAX.

BEST AVAILABLE COPY

X 3-303-1

| PREPARED BY BK, JN | | | TITLE PRE-PRODUCTION TESTS | | | | TYPE RV11 RV12 | | DWG. NO. B | | TABLE V | |
|-----------------------------|------|--------|----------------------------|-------------------------|--------|--|----------------------|--|------------|--|---------|--|
| CHECKED BY | | | | | | | | | DATE | | 9-18-61 | |
| APPROVED BY | | | | | | | | | | | | |
| RESISTANCE & SPEC. DATA NO. | | SOLDER | ROTATION, FL @ 125°C | | | | | | | | | |
| | | ±2% | 12R _T | 5%R _T | ±5% | | | | | | | |
| | | %DR | ENR INT %R _T | ENR INT %R _T | %DR | | | | | | | |
| RV12 2W | AV | +0.10 | 0.34 | 1.19 | +4.38 | | | | | | | |
| 70K Ω | SPAN | +0.52 | 0.51 | 2.56 | +6.93 | | | | | | | |
| 2 \pm 0Z. | | 0 | 0.27 | 0.54 | +1.39 | | | | | | | |
| 11106 | FAIL | 0 | 0 | 0 | 2 | | | | | | | |
| RV12 2W | AV | +0.05 | 1.16 | 3.16 | +4.99 | | | | | | | |
| 70K Ω | SPAN | +0.06 | 3.2 | 3.90 | +7.12 | | | | | | | |
| 1 \pm 0Z. | | 0 | 0.2 | 2.64 | +2.62 | | | | | | | |
| 11107 | FAIL | 0 | 0 | 1 | 2 | | | | | | | |
| RV11 1/2W | AV | +0.27 | 0.60 | 0.55 | +4.75 | | | | | | | |
| 1PC | SPAN | +0.47 | 0.89 | 1.06 | +6.07 | | | | | | | |
| 350K Ω | | -0.18 | 0.49 | 0.16 | +3.00 | | | | | | | |
| 1 \pm 0Z. | FAIL | 0 | 0 | 0 | 2 | | | | | | | |
| 11109 | | 0 | 0 | 0 | 4 | | | | | | | |
| RV11 1/2W | AV | +0.23 | 0.64 | 1.0 | +6.53 | | | | | | | |
| 1PC | SPAN | +0.32 | 0.91 | 2.31 | +10.34 | | | | | | | |
| 350K Ω | | +0.06 | 0.38 | 0.25 | +3.43 | | | | | | | |
| 2 \pm 0Z. | FAIL | 0 | 0 | 0 | 3 | | | | | | | |
| 11295 | | 0 | 0 | 0 | 4 | | | | | | | |
| RV11 1/2W | AV | +0.26 | | | | | | | | | | |
| 3PC | SPAN | +0.97 | | | | | | | | | | |
| 250K Ω | | +0.01 | | | | | | | | | | |
| 11108 | FAIL | 0 | | | | | | | | | | |
| | AV | | | | | | | | | | | |
| | SPAN | | | | | | | | | | | |
| | FAIL | | | | | | | | | | | |
| | AV | | | | | | | | | | | |
| | SPAN | | | | | | | | | | | |
| | FAIL | | | | | | | | | | | |
| | AV | | | | | | | | | | | |
| | SPAN | | | | | | | | | | | |
| | FAIL | | | | | | | | | | | |
| | AV | | | | | | | | | | | |
| | SPAN | | | | | | | | | | | |
| | FAIL | | | | | | | | | | | |
| | AV | | | | | | | | | | | |
| | SPAN | | | | | | | | | | | |
| | FAIL | | | | | | | | | | | |

3-303-1

PREPARED BY BK, JW

CHECKED BY

APPROVED BY

TITLE

PRE-PRODUCTION TESTS

| RESISTANCE & SPEC DATA NO. | | DC RESISTANCE | | | | TORQUE CZ IN | DIELECTRIC STRENGTH | ACCEL- ERATION % OR | SHOCK % OR | HI FREQUENCY VIBRATION | | LOW TEMP STORAGE & OP | |
|----------------------------------|------|-------------------------|--------------------------------|---------------------------|---------------------------|-----------------|------------------------|---------------------------|---------------|---------------------------|-------------------|--------------------------|------------|
| | | $\pm 5\%$ NOM | $\pm 10\%$ NOM | 70K 150K 350K | 50K 125K 250K | | | | | $\pm 2\%$ | $\pm 10\%$ | $\pm 2\%$ | $\pm 3\%$ |
| | | R _T Ω | MIN MAX % OF R _T | R _{MIN} Ω | R _{MAX} Ω | | | | | % OR TOTAL | % OR TRANSIENT | % OR STOR | % OR OP |
| RV12 70K Ω | AV | 73651 | 50.61 | 0.71 | 716 | 5.0 | NO BREAKDOWN | $\pm 3\%$ | $\pm 2\%$ | $\pm 2\%$ | $\pm 10\%$ | $\pm 2\%$ | $\pm 3\%$ |
| | SPAN | 76410 | 58.7 | 1.47 | 1963 | 5.5 | | $\pm 3\%$ | $\pm 2\%$ | $\pm 2\%$ | $\pm 10\%$ | $\pm 2\%$ | $\pm 3\%$ |
| | FAIL | 71310 | 45.74 | 0.91 | 46 | 4.5 | | $\pm 3\%$ | $\pm 2\%$ | $\pm 2\%$ | $\pm 10\%$ | $\pm 2\%$ | $\pm 3\%$ |
| 11114 | AV | 2 | 4 | 1 | 4 | 3 | 4 | 0 | 4 | 0 | 4 | 0 | 4 |
| RV11 1PC 350K Ω | AV | 353.92K | 44.6 | 972.2 | 172.7 | 1.5 | NO BREAKDOWN | $\pm 3\%$ | $\pm 2\%$ | $\pm 2\%$ | $\pm 10\%$ | $\pm 2\%$ | $\pm 3\%$ |
| | SPAN | 367.97K | 56.7 | 4859. | 863 | 1.7 | | $\pm 3\%$ | $\pm 2\%$ | $\pm 2\%$ | $\pm 10\%$ | $\pm 2\%$ | $\pm 3\%$ |
| | FAIL | 339.97K | 47.6 | .41 | .38 | 1.3 | | $\pm 3\%$ | $\pm 2\%$ | $\pm 2\%$ | $\pm 10\%$ | $\pm 2\%$ | $\pm 3\%$ |
| 11292 | AV | 1 | 5 | 1 | 5 | 0 | 5 | 0 | 5 | 0 | 5 | 0 | 5 |
| RV11 3PC 250K Ω | AV | 263.19K | 51.1 | 20.39 | 2.52 | 1.3 | NO BREAKDOWN | $\pm 3\%$ | $\pm 2\%$ | $\pm 2\%$ | $\pm 10\%$ | $\pm 2\%$ | $\pm 3\%$ |
| | SPAN | 272.12K | 59.7 | 19.9 | 6.7 | 1.3 | | $\pm 3\%$ | $\pm 2\%$ | $\pm 2\%$ | $\pm 10\%$ | $\pm 2\%$ | $\pm 3\%$ |
| | FAIL | 255.17K | 49.0 | .61 | .31 | 1.2 | | $\pm 3\%$ | $\pm 2\%$ | $\pm 2\%$ | $\pm 10\%$ | $\pm 2\%$ | $\pm 3\%$ |
| 11115 | AV | 1 | 3 | 1 | 3 | 0 | 3 | 0 | 3 | 0 | 3 | 0 | 3 |
| RV12 70K Ω | AV | 11577 | 10.5 | 3.07 | 109 | 2.2 | NO BREAKDOWN | $\pm 3\%$ | $\pm 2\%$ | $\pm 2\%$ | $\pm 10\%$ | $\pm 2\%$ | $\pm 3\%$ |
| | SPAN | 75370 | 51.61 | 11.55 | 426 | 4.5 | | $\pm 3\%$ | $\pm 2\%$ | $\pm 2\%$ | $\pm 10\%$ | $\pm 2\%$ | $\pm 3\%$ |
| | FAIL | 71900 | 45.90 | 1.25 | 296 | 2.0 | | $\pm 3\%$ | $\pm 2\%$ | $\pm 2\%$ | $\pm 10\%$ | $\pm 2\%$ | $\pm 3\%$ |
| 11112 | AV | 1 | 4 | 1 | 4 | 1 | 4 | 0 | 4 | 0 | 4 | 0 | 4 |
| RV11 1PC 350K Ω | AV | 345.79K | 47.16 | 34.6 | 437.9 | 1.9 | NO BREAKDOWN | $\pm 3\%$ | $\pm 2\%$ | $\pm 2\%$ | $\pm 10\%$ | $\pm 2\%$ | $\pm 3\%$ |
| | SPAN | 364.32K | 52.3 | 137 | 2187 | 2.2 | | $\pm 3\%$ | $\pm 2\%$ | $\pm 2\%$ | $\pm 10\%$ | $\pm 2\%$ | $\pm 3\%$ |
| | FAIL | 272.96K | 44.1 | .43 | .40 | 1.6 | | $\pm 3\%$ | $\pm 2\%$ | $\pm 2\%$ | $\pm 10\%$ | $\pm 2\%$ | $\pm 3\%$ |
| 11293 | AV | 1 | 5 | 1 | 5 | 1 | 5 | 0 | 5 | 0 | 5 | 0 | 5 |
| RV11 3PC 250K Ω | AV | 256.7K | 49.5 | 401.5 | 3.11 | 1.3 | NO BREAKDOWN | $\pm 3\%$ | $\pm 2\%$ | $\pm 2\%$ | $\pm 10\%$ | $\pm 2\%$ | $\pm 3\%$ |
| | SPAN | 266.94K | 51.3 | 832.4 | 4.7 | 1.5 | | $\pm 3\%$ | $\pm 2\%$ | $\pm 2\%$ | $\pm 10\%$ | $\pm 2\%$ | $\pm 3\%$ |
| | FAIL | 243.33K | 45.1 | .24 | .25 | 1.2 | | $\pm 3\%$ | $\pm 2\%$ | $\pm 2\%$ | $\pm 10\%$ | $\pm 2\%$ | $\pm 3\%$ |
| 11113 | AV | 1 | 3 | 1 | 3 | 0 | 3 | 0 | 3 | 0 | 3 | 0 | 3 |
| RV12 70K Ω | AV | 71770 | 51.91 | 5.40 | 108 | 4.44 | NO BREAKDOWN | $\pm 3\%$ | $\pm 2\%$ | $\pm 2\%$ | $\pm 10\%$ | $\pm 2\%$ | $\pm 3\%$ |
| | SPAN | 72920 | 55.25 | 10.40 | 206 | 5.25 | | $\pm 3\%$ | $\pm 2\%$ | $\pm 2\%$ | $\pm 10\%$ | $\pm 2\%$ | $\pm 3\%$ |
| | FAIL | 69000 | 45.42 | 5.33 | 11.4 | 5.25 | | $\pm 3\%$ | $\pm 2\%$ | $\pm 2\%$ | $\pm 10\%$ | $\pm 2\%$ | $\pm 3\%$ |
| 11116 | AV | 1 | 4 | 1 | 4 | 1 | 4 | 0 | 4 | 0 | 4 | 0 | 4 |
| RV11 1PC 350K Ω | AV | 253.84K | 47.9 | 1.26 | 1.55 | 1.5 | NO BREAKDOWN | $\pm 3\%$ | $\pm 2\%$ | $\pm 2\%$ | $\pm 10\%$ | $\pm 2\%$ | $\pm 3\%$ |
| | SPAN | 269.54K | 55.5 | 1.00 | .79 | 1.6 | | $\pm 3\%$ | $\pm 2\%$ | $\pm 2\%$ | $\pm 10\%$ | $\pm 2\%$ | $\pm 3\%$ |
| | FAIL | 249.26K | 49.3 | .53 | .77 | 1.4 | | $\pm 3\%$ | $\pm 2\%$ | $\pm 2\%$ | $\pm 10\%$ | $\pm 2\%$ | $\pm 3\%$ |
| 11117 | AV | 1 | 3 | 1 | 3 | 0 | 3 | 0 | 3 | 0 | 3 | 0 | 3 |
| | SPAN | | | | | | | | | | | | |
| | FAIL | | | | | | | | | | | | |
| | AV | | | | | | | | | | | | |
| | SPAN | | | | | | | | | | | | |
| | FAIL | | | | | | | | | | | | |
| | AV | | | | | | | | | | | | |
| | SPAN | | | | | | | | | | | | |
| | FAIL | | | | | | | | | | | | |

1

BEST AVAILABLE COPY

TYPE
RV11
RV12

DWG. NO. B

TABLE VI

DATE 9-18-61

| FREQUENCY VIBRATION | | TEMP STORAGE & OPER. | | TEMP CYCLE | SALT SPRAY | | | | | | | | | | |
|------------------------|----------|-------------------------|--------|---------------|---------------|--|--|--|--|--|--|--|--|--|--|
| 1% | ± 10% | ± 2% | ± 3% | ± 3% | | | | | | | | | | | |
| R | % OR | % OR | % OR | % OR | | | | | | | | | | | |
| AL | TERMINAL | % OR | % OR | % OR | | | | | | | | | | | |
| 13 | ± 0.79 | | | | | | | | | | | | | | |
| 02 | + 1.03 | | | | | | | | | | | | | | |
| 10 | - 1.11 | | | | | | | | | | | | | | |
| 4 | 0 | | | | | | | | | | | | | | |
| 27 | ± 0.39 | | | | | | | | | | | | | | |
| 30 | + 0.66 | | | | | | | | | | | | | | |
| | - 0.70 | | | | | | | | | | | | | | |
| 5 | 0 | | | | | | | | | | | | | | |
| 13 | ± 0.69 | | | | | | | | | | | | | | |
| 04 | + 0.98 | | | | | | | | | | | | | | |
| 21 | - 0.42 | | | | | | | | | | | | | | |
| 3 | 0 | | | | | | | | | | | | | | |
| | | + 0.15 | + 0.37 | + 0.84 | | | | | | | | | | | |
| | | + 0.31 | + 0.94 | + 1.14 | | | | | | | | | | | |
| | | + 0.02 | + 0.25 | - 0.11 | | | | | | | | | | | |
| | | 0 | 0 | 0 | | | | | | | | | | | |
| | | + 0.11 | + 0.49 | + 0.84 | | | | | | | | | | | |
| | | + 0.15 | + 0.35 | + 1.5 | | | | | | | | | | | |
| | | - 0.11 | - 0.15 | + 0.4 | | | | | | | | | | | |
| | | 0 | 0 | 0 | | | | | | | | | | | |
| | | + 0.06 | + 0.39 | + 1.0 | | | | | | | | | | | |
| | | + 0.02 | + 1.84 | + 1.6 | | | | | | | | | | | |
| | | - 0.11 | - 0.21 | + 0.6 | | | | | | | | | | | |
| | | 0 | 0 | 0 | | | | | | | | | | | |

* SALT SPRAY MECHANICALLY
OPERATIVE; SOME CORROSION
AT BUSHINGS & TERMINALS

2

TABLE VII

MOISTURE TESTS, UNHOUSED RVII ELEMENTS
10 Cycles

| Group No. | Termination of Material and Configuration | Original | Protective Film | %ΔR Ave. | Span | Failure Rate (≥±5%) |
|-----------|--|------------------------------|-----------------------------|-------------|----------------|---------------------------|
| | | Resistance Span- α | | | | |
| 1 | VZA + VLS, STD. SPRAY | 560K to 735K | DC200. 1000CS 50% TOLUOL | +4.91 | +0.47 to +25.1 | 2/10 |
| 2 | VZA + VLS, STD. SPRAY | 600K to 700K | DC3 | +6.45 | +1.0 to +26.3 | 2/9 |
| 3 | VZA + VLS, STD. SPRAY | 590K to 670K | TEFLON. rubbed on | +2.3 | +1.3 to +5.0 | 1/8 |
| 4 | VZA + VLS, STD. SPRAY | 570K to 680K | DC200. 0.65CS | +2.48 | +1.8 to +4.2 | 0/9 |
| 5 | VZA + VLS, STD. SPRAY | 590K to 690K | DESICOTE | +2.07 | +0.95 to +4.7 | 0/10 |
| 6 | VZA + VLS, STD. SPRAY | 535K to 635K | NONE | ±3.27 | -0.75 to +17.2 | 1/10 |
| 7 | VZA only. curved hop off | 315K to 575K | NONE | +3.8 | +1.8 to +9.2 | 2/10 |
| 8 | VZA + VLS (epoxy added) curved hop off | 275K to 760K | NONE | +2.0 | +0.31 to +3.3 | 0/10 |
| 9 | VLS (epoxy added), STD. SPRAY | 310K to 865K | NONE | ±1.77 | -0.6 to +3.1 | 0/10 |
| 10 | VZA + 10K/□ ink (epoxy added) STD. SPRAY | 300K to 820K | NONE | +1.92 | +0.15 to +3.3 | 0/10 |

BEST AVAILABLE COPY

BEST AVAILABLE COPY